
# K-HOCHLEIST SCHALLDAEMP

High-performance silencers

## Osobine

| | |
|---|---|
| **Radna temperatura** | -10 °C to +90 °C |
| **Položaj ugradnje** | Any |
| **Nagomilani pritisak (ulaz)** | Max. 6 bar |
| **Materijal** | Steel housing powder coated, perforated sheet galvanized steel, polyester felt discs |




## Napomena

Ostali podaci na upit.

## Opis

Multi-chamber silencers with a high blow-off rate, short exhaust time and excellent silencing effect.

## Artikal

| Naziv | Protok 6bara | Navoj | A (mm) | B (mm) | C (mm) |
|---|---|---|---|---|---|
| **K- 07 40 14 31** | 13350 l/min | G 1/2 | 14,0 | 103,0 | 80,0 |
| **K- 07 40 14 32** | 16700 l/min | G 3/4 | 16,0 | 106,0 | 80,0 |
| **K- 07 40 14 33** | 23350 l/min | G 1 | 18,0 | 130,0 | 110,0 |
| **K- 07 40 14 34** | 31700 l/min | G 1 1/4 | 20,0 | 136,0 | 110,0 |
| **K- 07 40 14 35** | 53400 l/min | G 1 1/2 | 24,0 | 168,0 | 150,0 |
| **K- 07 40 14 36** | 56700 l/min | G 2 | 24,0 | 168,0 | 150,0 |

*Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.*