

K-SCHLAUCHTUELLEN ES



Hose fittings

HANSA FLEX

Osobine

Radni pritisak Max. 20 bar

Materijal plemeniti čelik 1.4571



Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.

Ostali podaci na upit.

Dodatne informacije

Further types and dimensions on request.

Artikal

| Naziv | za crevo | za prekopnu navrtku | L1 (mm) | L2 (mm) |
|----------------|----------|---------------------|------------|------------|
| K- 07 40 16 51 | LW 6 mm | G 1/8 | 33,5 | 6,0 |
| K- 07 40 16 44 | LW 4 mm | G 1/4 | 47,0 | 13,5 |
| K- 07 40 16 45 | LW 6 mm | G 1/4 | 47,0 | 13,5 |
| K- 07 40 16 46 | LW 9 mm | G 1/4 | 47,0 | 14,0 |
| K- 07 40 16 47 | LW 6 mm | G 3/8 | 48,5 | 15,0 |
| K- 07 40 16 48 | LW 9 mm | G 3/8 | 48,5 | 15,0 |
| K- 07 40 16 49 | LW 9 mm | G 1/2 | 48,5 | 15,0 |
| K- 07 40 16 50 | LW 13 mm | G 1/2 | 48,5 | 15,0 |