

K-DOPPELNIPPEL AG-K MS

Detachable double nipples brass

HANSA FLEX

Osobine

| | |
|---------------------|---------------------------------|
| Radni pritisak | 10 bar |
| Temperatura medija | max. +90 °C |
| Temperatura okoline | Max. +90 °C |
| Materijal | Brass with a bare metal surface |



Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Ostali podaci na upit.

Dodatne informacije

Further types and dimensions on request.

Artikal

| Naziv | Navoj 1 | Navoj 2 | L1 (mm) | SW | SW1 (mm) |
|----------------|---------|---------|------------|-------|-------------|
| K- 07 40 00 33 | R 1/8 | R 1/8 | 27,0 | 15 mm | 5 |
| K- 07 40 00 39 | R 1/8 | R 1/4 | 30,0 | 15 mm | 5 |
| K- 07 40 00 34 | R 1/4 | R 1/4 | 33,5 | 19 mm | 6 |
| K- 07 40 00 40 | R 1/4 | R 3/8 | 34,5 | 19 mm | 6 |
| K- 07 40 00 35 | R 3/8 | R 3/8 | 36,5 | 22 mm | 8 |
| K- 07 40 00 36 | R 1/2 | R 1/2 | 44,0 | 27 mm | 12 |
| K- 07 40 00 37 | R 3/4 | R 3/4 | 53,0 | 36 mm | 14 |
| K- 07 40 00 38 | R 1 | R 1 | 63,5 | 46 mm | 19 |