

# K-KM MS

Hexagonal lock nuts, brass

## Osobine

|                     |             |
|---------------------|-------------|
| Radni pritisak      | 10 bar      |
| Temperatura medija  | max. +90 °C |
| Temperatura okoline | Max. +90 °C |



## Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Ostali podaci na upit.

## Dodatne informacije

Further types and dimensions on request.

## Artikal

| Naziv          | Navoj      | L1<br>(mm) | SW    |
|----------------|------------|------------|-------|
| K- 07 40 34 45 | G 1/8      | 3,5        | 15 mm |
| K- 07 40 34 46 | G 1/4      | 3,5        | 17 mm |
| K- 07 40 34 47 | G 3/8      | 4,5        | 19 mm |
| K- 07 40 34 48 | G 1/2      | 5,0        | 24 mm |
| K- 07 40 34 49 | G 3/4      | 5,0        | 32 mm |
| K- 07 40 34 50 | G 1        | 6,0        | 41 mm |
| K- 07 40 44 33 | G 1 1/4    | 8,5        | 50 mm |
| K- 07 40 44 34 | G 1 1/2    | 8,5        | 60 mm |
| K- 07 40 44 35 | G 2        | 11,0       | 70 mm |
| K- 07 40 34 51 | M 10 x 1   | 4,0        | 14 mm |
| K- 07 40 34 52 | M 12 x 1   | 5,0        | 17 mm |
| K- 07 40 34 54 | M 14 x 1   | 4,0        | 19 mm |
| K- 07 40 34 55 | M 16 x 1   | 5,0        | 22 mm |
| K- 07 40 34 56 | M 20 x 1,5 | 4,5        | 27 mm |
| K- 07 40 34 57 | M 22 x 1   | 4,5        | 27 mm |
| K- 07 40 34 58 | M 28 x 1,5 | 6,0        | 36 mm |