

K-XVM ZYL POM BLAU


Male connectors, parallel male thread

HANSA FLEX

Osobine

Radni pritisak 0 - 10 bar

Temperaturni opseg -10 °C to +60 °C



Napomena

Ostali podaci na upit.

Artikal

| Naziv | Navoj | za crevo | L1 (mm) | SW |
|----------------|-------|--------------|------------|-------|
| K- 07 40 33 15 | G 1/8 | 6 mm / 4 mm | 28,0 | 13 mm |
| K- 07 40 33 16 | G 1/8 | 8 mm / 6 mm | 29,5 | 13 mm |
| K- 07 40 33 17 | G 1/4 | 6 mm / 4 mm | 31,0 | 17 mm |
| K- 07 40 33 18 | G 1/4 | 8 mm / 6 mm | 32,0 | 17 mm |
| K- 07 40 33 19 | G 1/4 | 12 mm / 9 mm | 37,5 | 19 mm |
| K- 07 40 33 20 | G 1/4 | 10 mm / 8 mm | 34,0 | 17 mm |
| K- 07 40 33 21 | G 3/8 | 8 mm / 6 mm | 34,0 | 19 mm |
| K- 07 40 33 22 | G 3/8 | 10 mm / 8 mm | 35,5 | 19 mm |
| K- 07 40 33 23 | G 3/8 | 12 mm / 9 mm | 37,5 | 19 mm |