
K-PROP VENTIL WA 24 V DC

Proportional valves for controlling the flow of water / oil, 24 VDC, closed when de-energised



Osobine Temperaturni opseg Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8) Mediji Air, neutral gases, water, oil Područje pritiska Vacuum (max. 8 bar) Upravljanje Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA Ponašanje Failsafe Tight closure in case of loss of voltage
Mediji Air, neutral gases, water, oil Područje pritiska Vacuum (max. 8 bar) Upravljanje Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA
Područje pritiska Vacuum (max. 8 bar) Upravljanje Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA
Upravljanje Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA
mA
Ponašanje Failsafe Tight closure in case of loss of voltage
Kućište, sedište ventila Brass
Unutrašnji delovi Stainless steel
Ventilska pečurka FKM
Zaptivni materijal FKM
Zaptivni materijal FKM





Napomena

Ostali podaci na upit.

Opis

Dodatne informacije

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Naziv	Priključak	DN	maks. razlika u radnom pritisku (bar)	A (mm)	В	C (mm)
K- 07 25 09 95	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 96	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 97	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 98	G 3/8	7	1	85,0	48,0 mm	97,0

18.10.2025 HANSA-FLEX AG www.hansa-flex.com