

K-FLASCHENDRUCKR 200 N GASE

Regulator pritiska flaše, pritisak flaše 200 bar, za nezapaljive gasove


HANSA FLEX

Osobine

Manometar sadržaja 0 - 200/315 bar (max. cylinder pressure 200 bar),
0 - 300/400 bar (max. cylinder pressure 300 bar),
0 - 18/40 bar for acetylene

Materijal presovani mesing

Priključak za flašu Nut 3/4



Napomena

Ostali podaci na upit.

Opis

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Artikal

Naziv	Vrsta gasa	Radni pritisak bar
K- 07 25 07 11	Oxygen	0 - 10,0 bar
K- 07 25 07 12	Oxygen	0 - 20,0 bar
K- 07 25 07 14	Compressed air	0 - 10,0 bar
K- 07 25 07 15	Compressed air	0 - 20,0 bar
K- 07 25 07 16	Nitrogen	0 - 10,0 bar
K- 07 25 07 17	Nitrogen	0 - 20,0 bar
K- 07 25 07 18	Carbon dioxide	0 - 10,0 bar
K- 07 25 07 19	Carbon dioxide	0 - 20,0 bar
K- 07 25 07 20	Argon/helium	0 - 10,0 bar

Rezervni delovi

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	Zaštitni poklopci