


# K-NEBELOEL PC-BEHÄEL SCHUTZK HANSA

Oil-mist lubricators

**HANSA FLEX**

## Osobine

|                           |   |
|---------------------------|---|
| Ulazni pritisak           | 0.5 - 16 bar                                    |
| Temperaturni opseg        | -10 °C to +50 °C                                |
| Mediji                    | Komprimovani vazduh                             |
| Zaptivni materijal        | NBR   |
| Prikjučni navoj           | Material: Die-cast zinc                         |
| Posuda                    | Polycarbonate (with bayonet lock)               |
| Kučište                   | Material: Grivory® (PA 66)                      |
| Zavrtanj                  | Polyamide                                       |
| Naglavak za kapljanje     | PA  |
| Vrsta ulja                | CL 32 acc. to DIN 51517 - ISO VG 32             |
| Merenje vrednosti protoka | At P2 = 6 bar, pressure drop $\Delta p = 1$ bar |



## Napomena

Ostali podaci na upit.

## Opis

Oil-mist lubricators with excellent flow rates in modern design. These devices can be used to top up oil automatically. A hose must be connected to the threaded nipple on the oil bowl for this purpose. When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

## Artikal

| Naziv          | Navoj | Protok (L/min) | A (mm) | B        | C (mm) |
|----------------|-------|----------------|--------|----------|--------|
| K- 07 25 08 79 | G 1/4 | 2800           | 52,0   | 183,0 mm | 62,2   |
| K- 07 25 08 80 | G 3/8 | 2800           | 52,0   | 183,0 mm | 62,2   |
| K- 07 25 08 81 | G 3/8 | 8000           | 63,0   | 208,2 mm | 69,7   |
| K- 07 25 08 82 | G 1/2 | 8000           | 63,0   | 208,2 mm | 69,7   |
| K- 07 25 08 77 | G 3/4 | 16000          | 85,0   | 270,4 mm | 87,9   |
| K- 07 25 08 78 | G 1   | 16000          | 85,0   | 270,4 mm | 87,9   |

## Rezervni delovi

|                              |                               |
|------------------------------|-------------------------------|
| K-HALTERBAUSATZ HANSA        | Holder HANSA                  |
| K-ERSATZBEHAELTER HANSA POLY | Spare tank HANSA polycarbonat |
| K-TROPFAUFSATZ HANSA         | Drip attachment HANSA         |