

K-ANFAV MULTIFIX MINI

Start-up valves

HANSA FLEX

Osobine

| | |
|---------------------------|--|
| Ulazni pritisak | Min. 2.5 bar, max. 16 bar |
| Temperatura medija | max. 60 °C |
| Temperatura okoline | Max. 60 °C |
| Protok | 1600 l/min |
| Zaptivni materijal | NBR |
| Kućište | Die-cast zinc |
| Merenje vrednosti protoka | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Napomena

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

Ostali podaci na upit.

Opis

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. The full cross-section of the regulator is opened at 50% of the input pressure. With adjustable restrictor!

Artikal

| Naziv | Navoj | A (mm) | B | C (mm) | D (mm) |
|----------------|-------|-----------|---------|-----------|-----------|
| K- 07 25 11 53 | G 1/4 | 45,0 | 77,5 mm | 48,5 | 29,0 |

Pribor

K-HALTERBAUSATZ Holder

Rezervni delovi

K-KOPPELPAKET MEHR Coupling packet