


K-WTEH KOMBI PC-BEHÄLTER S H ABLV

Combination service units with polycarbonate bowl, bowl guard and manual drain valve

HANSA FLEX

Osobine

| | |
|--------------------------------|--|
| Ulazni pritisak | Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl) |
| Temperatura medija | max. 50 °C |
| Temperatura okoline | Max. 50 °C |
| Širina pora u elementu filtera | 50 µm |
| Zaptivni materijal | NBR |
| Kućište | Die-cast zinc, Spring bonnet; PA |
| Naglavak za kapljanje | PA |
| Merenje vrednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



Napomena

Ostali podaci na upit.

Opis

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design. The pressure setting can be locked by pushing the knob down. Oil can be filled under pressure.

Artikal

| Naziv | Navoj | Opseg regulacije | Protok (L/min) | A (mm) | B | C (mm) |
|----------------|-------|------------------|----------------|--------|----------|--------|
| K- 07 25 08 45 | G 1/4 | 0.5 - 10 bar | 1400 | 67,0 | 217,0 mm | 68,5 |
| K- 07 25 08 47 | G 1/4 | 0.5 - 16 bar | 1000 | 67,0 | 217,0 mm | 68,5 |
| K- 07 25 08 49 | G 3/8 | 0.5 - 10 bar | 1400 | 67,0 | 217,0 mm | 68,5 |
| K- 07 25 08 51 | G 3/8 | 0.5 - 16 bar | 1000 | 67,0 | 217,0 mm | 68,5 |
| K- 07 25 08 53 | G 1/2 | 0.5 - 10 bar | 1400 | 65,0 | 217,0 mm | 68,5 |
| K- 07 25 08 55 | G 1/2 | 0.5 - 16 bar | 1000 | 65,0 | 217,0 mm | 68,5 |
| K- 07 25 08 57 | G 3/4 | 0.5 - 10 bar | 3400 | 97,0 | 296,5 mm | 96,5 |
| K- 07 25 08 59 | G 3/4 | 0.5 - 16 bar | 2800 | 97,0 | 296,5 mm | 96,5 |
| K- 07 25 08 61 | G 1 | 0.5 - 10 bar | 3400 | 93,0 | 296,5 mm | 96,5 |
| K- 07 25 08 63 | G 1 | 0.5 - 16 bar | 2800 | 93,0 | 296,5 mm | 96,5 |

Rezervni delovi

| | |
|--------------------------|--|
| K-HALTERBAUSATZ SERIE 81 | Holder for series 81 |
| K-ERSATZBEHÄLTER KOMBI | Spare tank |
| K-SCHUTZKORB G | Protective cage |
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-TROPFAUFSATZ POLYCARBO | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL | Drip attachment metal |
| K-FILTERELEMENT | Filter element |
| K-ABLASSVENTIL AUTO | Fully-automatic drain valve with Adapter G 1/8 |
| K-RD NIPPEL KURZ 1 | Reducing nipples, short type |
| K-XV AGM 2 | Double nipples, parallel male thread |