



K-SNV ENTLUE V SCHL GEW

Quick-exhaust valves, conveyed exhaust, pipe (input) - thread (output)

HANSA FLEX

Osobine

Radni pritisak	1 - 10 bar
Protok 6,3bara	50 NI/min (Ø 4), 270 NI/min (Ø 6), 400 NI/min (Ø 8)
Prot. Odzračivanje 6,3bara	100 NI/min (Ø 4), 700 NI/min (Ø 6), 1000 NI/min (Ø 8)
Temperaturni opseg	-20 °C to +60 °C
Telo	Technopolymer
Unutrašnji delovi	nickel-plated brass, brass, \ntechnopolymer, stainless steel
Zaptivni materijal	NBR
Montaža	Wall mounting (housing with drilled holes) Bracket mounting (mounting bracket available) Panel mounting (with bracket or lock nut)
Simbol	on the housing



Napomena

Ostali podaci na upit.

Opis

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design.
All components can be installed in parallel, in series, in a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

Artikal

Naziv	Navoj	Ø za crevo (mm)	A (mm)	B (mm)	l (mm)
K- 07 15 20 36	G 1/8	6	58,5	30,2	14,6
K- 07 15 20 37	G 1/8	8	66,2	35,9	18,7
K- 07 15 20 34	G 1/4	6	61,5	30,2	14,6
K- 07 15 20 35	G 1/4	8	70,6	35,9	18,7
K- 07 15 20 38	G 3/8	8	72,2	35,9	18,7