K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC

Osobine

Radni pritisak	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\ nMax. vacuum 10 bar (external pilot air)
Temperaturni opseg	-10 °C to +60 °C
Protok 6bara i 10bara	550 Nl/min
Protok 6bara i 5bara	400 Nl/min
Telo ventila	Aluminijum
Opruga	Special steel
Klipovi	Aluminium
Zaptivni materijal	NBR



Napomena

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Ostali podaci na upit.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikal

Naziv	Priključak	Simbol	Aktiviranje	Položaji elementa za uključivanje
K- 07 15 00 78	G 1/8	5	monostable	2
K- 07 15 00 79	G 1/8	6	bistabilno	2
K- 07 15 00 80	G 1/8	7	monostable	3*
K- 07 15 00 81	G 1/8	8	bistabilno	3*

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.