

K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

HANSA FLEX

Osobine

| | |
|-----------------------|---|
| Radni pritisak | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Temperaturni opseg | -10 °C to +60 °C |
| Protok 6bara i 10bara | 550 NI/min |
| Protok 6bara i 5bara | 400 NI/min |
| Telo ventila | Aluminijum |
| Opruga | Special steel |
| Klipovi | Aluminium |
| Zaptivni materijal | NBR |



Napomena

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.

Ostali podaci na upit.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikal

| Naziv | Priključak | Simbol | Aktiviranje | Položaji elementa za uključivanje |
|----------------|------------|--------|-------------|-----------------------------------|
| K- 07 15 00 82 | G 1/8 | 9 | monostable | 2 |
| K- 07 15 00 83 | G 1/8 | 10 | bistabilno | 2 |
| K- 07 15 00 84 | G 1/8 | 11 | monostable | 3* |
| K- 07 15 00 85 | G 1/8 | 12 | bistabilno | 3* |