

K-WV 5/2 MANU K DREHHEBEL

5/2-way pilot valves, manually operated, with short wing lever

HANSA FLEX

Osobine

| | |
|-----------------------|---|
| Radni pritisak | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Temperaturni opseg | -10 °C to +60 °C |
| Protok 6bara i 10bara | 550 NI/min |
| Protok 6bara i 5bara | 400 NI/min |
| Telo ventila | Aluminijum |
| Opruga | Special steel |
| Klipovi | Aluminium |
| Zaptivni materijal | NBR |



Napomena

*3 valve positions only in conjunction with a second way valve.

Ostali podaci na upit.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikal

| Naziv | Priključak | Simbol | Aktiviranje | Položaji elementa za uključivanje |
|----------------|------------|--------|-------------|-----------------------------------|
| K- 07 15 02 37 | G 1/8 | 5 | monostable | 2 |
| K- 07 15 02 38 | G 1/8 | 6 | bistabilno | 2 |
| K- 07 15 02 39 | G 1/8 | 7 | monostable | 3* |
| K- 07 15 02 40 | G 1/8 | 8 | bistabilno | 3* |