


# K-WV 3/2 PNEUMATISCH

3/2-way pilot valves

**HANSA FLEX**

## Osobine

Radni pritisak	Max. vacuum 10 bar
min. radni pritisak	2.5 bar (monostable), 1.0 bar (bistable)
Temperaturni opseg	-10 °C to +60 °C
Protok 6bara i 10bara	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
Protok 6bara i 5bara	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)
Priključak upravljačkog vazduha	G 1/8



## Napomena

Ostali podaci na upit.

## Artikal

Naziv	Priključak	DN	Funkcija	Broj plana uključivanja	Upravljanje
K- 07 15 00 41	G 1/8	5	3/-way NO	24	
K- 07 15 00 42	G 1/4	8	3/-way NO	24	
K- 07 15 00 45	G 1/2"	15	3/-way NO	24	
K- 07 15 25 67	G 3/8	13	3/-way NO	24	
K- 07 15 00 43	G 1/8	5	3/2-way NC	25	
K- 07 15 00 44	G 1/4	8	3/2-way NC	25	
K- 07 15 00 46	G 1/2"	15	3/2-way NC	25	
K- 07 15 25 68	G 3/8	13	3/2-way NC	25	
K- 07 15 00 47	G 1/8	5	3/2-way	26	
K- 07 15 00 48	G 1/4	8	3/2-way	26	
K- 07 15 00 49	G 1/2"	15	3/2-way	26	
K- 07 15 25 69	G 3/8	13	3/2-way	26	