

K-WV 3/2 PNEUMATISCH

3/2-way pilot valves

HANSA FLEX

Osobine

| | |
|---------------------------------|--|
| Radni pritisak | Max. vacuum 10 bar |
| min. radni pritisak | 2.5 bar (monostable), 1.0 bar (bistable) |
| Temperaturni opseg | -10 °C to +60 °C |
| Protok 6bara i 10bara | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Protok 6bara i 5bara | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |
| Priključak upravljačkog vazduha | G 1/8 |



Napomena

Ostali podaci na upit.

Artikal

| Naziv | Priključak | DN | Funkcija | Broj plana uključivanja | Upravljanje |
|----------------|------------|----|------------|-------------------------|-------------|
| K- 07 15 00 41 | G 1/8 | 5 | 3/-way NO | 24 | |
| K- 07 15 00 42 | G 1/4 | 8 | 3/-way NO | 24 | |
| K- 07 15 00 45 | G 1/2" | 15 | 3/-way NO | 24 | |
| K- 07 15 25 67 | G 3/8 | 13 | 3/-way NO | 24 | |
| K- 07 15 00 43 | G 1/8 | 5 | 3/2-way NC | 25 | |
| K- 07 15 00 44 | G 1/4 | 8 | 3/2-way NC | 25 | |
| K- 07 15 00 46 | G 1/2" | 15 | 3/2-way NC | 25 | |
| K- 07 15 25 68 | G 3/8 | 13 | 3/2-way NC | 25 | |
| K- 07 15 00 47 | G 1/8 | 5 | 3/2-way | 26 | |
| K- 07 15 00 48 | G 1/4 | 8 | 3/2-way | 26 | |
| K- 07 15 00 49 | G 1/2" | 15 | 3/2-way | 26 | |
| K- 07 15 25 69 | G 3/8 | 13 | 3/2-way | 26 | |