

# K-VORFILTER PC-BEHÄLTER MULTIFIX

Pre-filters with polycarbonate bowl

**HANSA FLEX**

## Osobine

Ulazni pritisak	Max. 16 bar
Temperatura medija	max. 60 °C
Temperatura okoline	Max. 60 °C
Filterska jedinica	0,30 µm
Stepen dejstva	99.999 %
Zaptivni materijal	NBR
Uložak filtera	Paper-POM
Kućište	Die-cast zinc
Drain valve	Semi-automatic
Merenje vrednosti protoka	FV at P1 = 6 bar and $\Delta p = 0.02$ bar



## Napomena

\* = Dimensions with adapter plate!

Ostali podaci na upit.

## Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Dodatne informacije

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

## Artikal

Naziv	Navoj	Protok (L/min)	A (mm)	B	C (mm)	D (mm)	DN
K- 07 25 10 68	G 1/4	160	47,8	152,1 mm	27,0	125,1	6
K- 07 25 10 71	G 1/2	500	68,8	180,8 mm (185,8 mm)*	72,0	147,3	15

## Rezervni delovi

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-PC-BEHÄLTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHÄLTER OELER MULTIFIX	Metal tank oiler