


K-FI AK KOH PC-BEHÄEL S MULTIFIX

Activated carbon filters with polycarbonate bowl and bowl guard

HANSA FLEX

Osobine

Ulazni pritisak	Max. 16 bar
Temperatura medija	max. 60 °C
Temperatura okoline	Max. 60 °C
Zaptivni materijal	NBR
Uložak filtera	Activated carbon-POM
Kućište	Die-cast zinc
Drain valve	Semi-automatic
Sadržaj preostalog ulja	0.005 mg/m ³
Merenje vrednosti protoka	FA at P1 = 6 bar and $\Delta p = 0.2$ bar



Napomena

Ostali podaci na upit.

Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Artikal

Naziv	Navoj	Protok (L/min)	A (mm)	B (mm)	C (mm)	D (mm)	DN	Konstrukciona veličina
K- 07 25 10 50	G 1/4	380	47,8	136,8 mm	27,0	109,8	6	1
K- 07 25 10 53	G 1/2	1500	68,8	167,0 mm	34,5	132,5	15	2

Rezervni delovi

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-PC-BEHÄELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHÄELTER OELER MULTIFIX	Metal tank oiler