


K-FI MIKRO PC-BEHÄEL SCHU MULTIFIX

Micro-filters with polycarbonate bowl and bowl guard

HANSA FLEX

Osobine

Ulazni pritisak	Max. 16 bar
Temperatura medija	max. 60 °C
Temperatura okoline	Max. 60 °C
Filterska jedinica	0,01 µm
Stepen dejstva	99.999 %
Zapivni materijal	NBR
Uložak filtera	Borosilicate-POM
Kućište	Die-cast zinc
Drain valve	Semi-automatic
Merenje vrednosti protoka	FM at P1 = 6 bar and $\Delta p = 0.09$ bar



Napomena

* = Dimensions with adapter plate!
Ostali podaci na upit.

Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Dodatne informacije

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

Artikal

Naziv	Navoj	Protok (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Konstrukciona veličina
K- 07 25 10 60	G 1/4	280	47,8	152,1 mm	27,0	125,1	6	1
K- 07 25 10 63	G 1/2	720	68,8	180,8 mm (185,8 mm)*	72,0	147,3	15	2

Rezervni delovi

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-PC-BEHÄELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHÄELTER OELER MULTIFIX	Metal tank oiler