


K-FI MIKRO PC-BEHAEL SCHU MULTIFIX

Micro-filters with polycarbonate bowl and bowl guard

HANSA FLEX

Osobine

| | |
|---------------------------|--|
| Ulazni pritisak | Max. 16 bar |
| Temperatura medija | max. 60 °C |
| Temperatura okoline | Max. 60 °C |
| Filterska jedinica | 0,01 µm |
| Stepen dejstva | 99.999 % |
| Zaptivni materijal | NBR |
| Uložak filtera | Borosilicate-POM |
| Kućište | Die-cast zinc |
| Drain valve | Semi-automatic |
| Merenje vrednosti protoka | FM at P1 = 6 bar and $\Delta p = 0.09$ bar |



Napomena

* = Dimensions with adapter plate!

Ostali podaci na upit.

Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Dodatne informacije

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

Artikal

| Naziv | Navoj | Protok (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Konstrukciona veličina |
|----------------|-------|----------------|--------|----------------------|--------|--------|----|------------------------|
| K- 07 25 10 60 | G 1/4 | 280 | 47,8 | 152,1 mm | 27,0 | 125,1 | 6 | 1 |
| K- 07 25 10 63 | G 1/2 | 720 | 68,8 | 180,8 mm (185,8 mm)* | 72,0 | 147,3 | 15 | 2 |

Rezervni delovi

| | |
|----------------------------------|---------------------------|
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler |