

K-LKM S NW7,6 IG

Safety couplings DN 7.6, female

Osobine

Radni pritisak	Max. 16 bar
Protok vazduha	2.250 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +100 °C
Materijal	Galvanised steel / brass
Opruga	Stainless-steel
Zaptivni materijal	NBR



Napomena

Ostali podaci na upit.

Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rates and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414.

Artikal

Naziv	Priključak	Dužina (mm)	SW (mm)
K- 07 35 13 20	G 1/4 female	57,1	20
K- 07 35 13 22	G 3/8 female	60,1	22
K- 07 35 13 17	G 1/2 female	59,5	25

Dodatni elementi

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel