

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Osobine

Radni pritisak	0 - 35 bar
Temperatura medija	-20 °C to +100 °C
Kućište	Brass
Osigurač i zaptivka	Industrial glue, mid hardened



Napomena

Couplings and distributors are also available separately
Ostali podaci na upit.

Opis

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Dodatne informacije

Couplings and distributors are also available separately

Artikal

Naziv	Priključak	Spojnice	sastoji se od razvodnika
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

je oprema za sledeće proizvode

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«