

# K-S-BKR M ENTL ABSCHL

Safety ball valves lockable, with relief port

**HANSA FLEX**

## Osobine

|                       |                              |
|-----------------------|------------------------------|
| Radni pritisak        | maks. 10 bara                |
| Radna temperatura     | -20 °C to max. +100 °C       |
| Otvor za odzračivanje | M 5                          |
| Opis navoja           | Rp thread acc. to ISO 7-1    |
| Ručna poluga          | Stainless steel - PVC coated |
| Zaptivka kugle        | PTFE / NBR                   |
| Zaptivka vretena      | PTFE                         |
| Materijal             | plemeniti čelik              |



## Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Ostali podaci na upit.

## Opis

2/2-way stainless steel safety ball valves. Specially designed for pneumatic applications. The ball valve can be locked manually and has a relief port.

## Dodatne informacije

The price does not include a padlock. Please order separately.

## Artikal

| Naziv          | DN | Navoj    | A<br>(mm) | B<br>(mm) | L<br>(mm) |
|----------------|----|----------|-----------|-----------|-----------|
| K- 07 30 15 16 | 8  | Rp 1/4   | 100,0     | 50,0      | 55,0      |
| K- 07 30 15 17 | 10 | Rp 3/8   | 100,0     | 50,0      | 55,0      |
| K- 07 30 15 18 | 15 | Rp 1/2   | 130,0     | 60,0      | 65,0      |
| K- 07 30 15 19 | 20 | Rp 3/4   | 130,0     | 64,0      | 74,6      |
| K- 07 30 15 20 | 25 | Rp 1     | 165,0     | 71,0      | 88,0      |
| K- 07 30 15 21 | 32 | Rp 1 1/4 | 165,0     | 78,0      | 102,0     |
| K- 07 30 15 22 | 40 | Rp 1 1/2 | 190,0     | 86,0      | 110,0     |
| K- 07 30 15 23 | 50 | Rp 2     | 190,0     | 95,0      | 125,0     |

## Pribor

K-VORHAENGESCHLOSS Padlock