

K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

HANSA FLEX

Osobine

| | |
|--------------------|--|
| Radna struja | 200 mA |
| Navojni spoj kabla | M 20 x 1.5 |
| Uključna funkcija | Positive switching, PNP NO contact, damped or undamped in the end position |
| Vrsta zaštite | IP 67, acc. to DIN EN 60529 |
| Temperaturni opseg | -20 °C to +70 °C |
| Kućište | Polyamide blue or black |
| Zavrtnaj | Stainless steel 1.4301 |
| Osovina | Polyamide PA6, black |
| Poklopac | Polycarbonate, transparent |
| Montažni most | PA6 with 30 % glass fibre |
| Zaptivke | EPDM and NBR |
| Zaptivni materijal | NBR |



Napomena

Ostali podaci na upit.

Opis

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Artikal

| Naziv | Napon | Definicija |
|----------------|---------------|---|
| K- 07 30 29 06 | 9 V - 36 V DC | End position feedback, D 2 type with inductive 3-wire sensors |