K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

Osobine

Radna struja	200 mA
Navojni spoj kabla	M 20 x 1.5
Uključna funkcija	Positive switching, PNP NO contact, damped or undamped in the end position
Vrsta zaštite	IP 67, acc. to DIN EN 60529
Temperaturni opseg	-20 °C to +70 °C
Kućište	Polyamide blue or black
Zavrtanj	Stainless steel 1.4301
Osovina	Polyamide PA6, black
Poklopac	Polycarbonate, transparent
Montažni most	PA6 with 30 % glass fibre
Zaptivke	EPDM and NBR
Zaptivni materijal	NBR



Napomena

Ostali podaci na upit.

Opis

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Artikal

Naziv	Napon	Definicija
K- 07 30 29 06	9 V - 36 V DC	End position feedback, D 2 type with inductive 3-wire sensors

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.