K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

Osobine

Verzija	Calibration, testing and service unit
Tačnost	0,25% FS
Temperatura mernog materijala	-20 °C to +80 °C
Temperatura okoline	-10 °C to +50 °C
Delovi koji dodiruju merni materijal	CrNi-steel with NBR seal
Kućište	Die-cast zinc



Napomena

Ostali podaci na upit.

Opis

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

Dodatne informacije

Further measuring ranges on request

Artikal

Naziv	Merni opseg	Priključak
K- 07 20 12 70	-0.95 / +40 bar	G 1/4

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.