

## Osobine

Temperatura okoline	-20 °C to +80 °C
Priključak na električnu mrežu	Okrugla utikačka spojnica M 12 x 1, 4-polna
Izlazni signal	2 switching outputs
Tačnost	1% of span
Pomoćna energija	DC 15 - 35V
Delovi koji dodiruju merni materijal	CrNi steel
Temperatura mernog materijala	-20 °C to +85 °C
Procesni priključak	G 1/4
Vrsta zaštite	IP 65 and IP 67 (M 12 x 1)
Kućičšte	CrNi steel



## Napomena

Ostali podaci na upit.

## Opis

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air. Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

## Artikal

Naziv	Priključak	Merni opseg
K- 07 30 30 07	G 1/4	0 - 1.0 bar
K- 07 30 30 12	G 1/4	0 - 2.5 bar
K- 07 30 30 15	G 1/4	0 - 4.0 bar
K- 07 30 30 18	G 1/4	0 - 6.0 bar
K- 07 30 30 08	G 1/4	0 - 10.0 bar
K- 07 30 30 10	G 1/4	0 - 16.0 bar
K- 07 30 30 13	G 1/4	0 - 25.0 bar
K- 07 30 30 16	G 1/4	0 - 40.0 bar
K- 07 30 30 19	G 1/4	0 - 60.0 bar
K- 07 30 30 09	G 1/4	0 - 100.0 bar
K- 07 30 30 11	G 1/4	0 - 160.0 bar
K- 07 30 30 14	G 1/4	0 - 250.0 bar
K- 07 30 30 17	G 1/4	0 - 400.0 bar
K- 07 30 30 20	G 1/4	0 - 600.0 bar

## Pribor

K-ELEKTRO DRUCHSCHALTER EDS    Electronic pressure switch EDS