

Osobine

| | |
|--------------------------------------|---|
| Temperatura okoline | -20 °C to +80 °C |
| Priključak na električnu mrežu | Okrugla utikačka spojnica M 12 x 1, 4-polna |
| Izlazni signal | 2 switching outputs |
| Tačnost | 1% of span |
| Pomoćna energija | DC 15 - 35V |
| Delovi koji dodiruju merni materijal | CrNi steel |
| Temperatura mernog materijala | -20 °C to +85 °C |
| Procesni priključak | G 1/4 |
| Vrsta zaštite | IP 65 and IP 67 (M 12 x 1) |
| Kućiče | CrNi steel |



Napomena

Ostali podaci na upit.

Opis

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air. Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

Artikal

| Naziv | Priključak | Merni opseg |
|----------------|------------|---------------|
| K- 07 30 30 07 | G 1/4 | 0 - 1.0 bar |
| K- 07 30 30 12 | G 1/4 | 0 - 2.5 bar |
| K- 07 30 30 15 | G 1/4 | 0 - 4.0 bar |
| K- 07 30 30 18 | G 1/4 | 0 - 6.0 bar |
| K- 07 30 30 08 | G 1/4 | 0 - 10.0 bar |
| K- 07 30 30 10 | G 1/4 | 0 - 16.0 bar |
| K- 07 30 30 13 | G 1/4 | 0 - 25.0 bar |
| K- 07 30 30 16 | G 1/4 | 0 - 40.0 bar |
| K- 07 30 30 19 | G 1/4 | 0 - 60.0 bar |
| K- 07 30 30 09 | G 1/4 | 0 - 100.0 bar |
| K- 07 30 30 11 | G 1/4 | 0 - 160.0 bar |
| K- 07 30 30 14 | G 1/4 | 0 - 250.0 bar |
| K- 07 30 30 17 | G 1/4 | 0 - 400.0 bar |
| K- 07 30 30 20 | G 1/4 | 0 - 600.0 bar |

Pribor

K-ELEKTRO DRUCHSCHALTER EDS Electronic pressure switch EDS