

Osobine

Temperatura okoline	-20 °C to +80 °C
Priključak na električnu mrežu	Okrugla utikačka spojnica M 12 x 1, 4-polna
Izlazni signal	2 switching outputs
Tačnost	1% of span
Pomoćna energija	DC 15 - 35V
Delovi koji dodiruju merni materijal	CrNi steel
Temperatura mernog materijala	-20 °C to +85 °C
Procesni priključak	G 1/4
Vrsta zaštite	IP 65 and IP 67 (M 12 x 1)
Kućiče	CrNi steel



Napomena

Ostali podaci na upit.

Opis

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air. Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

Artikal

Naziv	Priključak	Merni opseg
K- 07 30 30 07	G 1/4	0 - 1.0 bar
K- 07 30 30 12	G 1/4	0 - 2.5 bar
K- 07 30 30 15	G 1/4	0 - 4.0 bar
K- 07 30 30 18	G 1/4	0 - 6.0 bar
K- 07 30 30 08	G 1/4	0 - 10.0 bar
K- 07 30 30 10	G 1/4	0 - 16.0 bar
K- 07 30 30 13	G 1/4	0 - 25.0 bar
K- 07 30 30 16	G 1/4	0 - 40.0 bar
K- 07 30 30 19	G 1/4	0 - 60.0 bar
K- 07 30 30 09	G 1/4	0 - 100.0 bar
K- 07 30 30 11	G 1/4	0 - 160.0 bar
K- 07 30 30 14	G 1/4	0 - 250.0 bar
K- 07 30 30 17	G 1/4	0 - 400.0 bar
K- 07 30 30 20	G 1/4	0 - 600.0 bar

Pribor

K-ELEKTRO DRUCHSCHALTER EDS Electronic pressure switch EDS