

# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,  
CrNi steel type

**HANSA FLEX**

## Osobine

Tip	233.50
Verzija	Glycerine-filled bourdon-tube pressure gauge, CrNi steel type
Primena	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Klasa kvaliteta	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
Temperatura medija	max. +100 °C
Temperatura okoline	-20 °C do +60 °C
Kućište	CrNi steel
Okno za kontrolu	Laminated safety glass Ø 63 = Polycarbonate



## Napomena

Ostali podaci na upit.

## Opis

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

## Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 11 93	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 11 95	-1 / +0.6 bar	63,0	G 1/4"
K- 07 20 11 97	-1 / +1.5 bar	63,0	G 1/4"
K- 07 20 11 99	-1 / +3.0 bar	63,0	G 1/4"
K- 07 20 12 01	-1 / +5.0 bar	63,0	G 1/4"
K- 07 20 12 03	-1 / +9.0 bar	63,0	G 1/4"
K- 07 20 12 05	-1 / +15.0 bar	63,0	G 1/4"
K- 07 20 12 08	0 - 1.0 bar	63,0	G 1/4"
K- 07 20 12 10	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 12 12	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 12 14	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 12 16	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 12 18	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 12 20	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 12 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 12 24	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 12 26	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 12 28	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 12 30	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 12 32	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 12 34	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 12 36	0 - 600.0 bar	63,0	G 1/4"
K- 07 20 11 92	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 12 09	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100,0	G 1/2"



# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,  
CrNi steel type

**HANSA FLEX**

Artikal			
Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 12 23	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160,0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160,0	G 1/2"