


K-WV 5/2 ELEKTROPNEU MONOSTABIL 4V

5/2-way pilot valve, monostable

HANSA FLEX

Osobine

Radni pritisak	1.5 - 8 bar
Temperaturni opseg	-20 °C to +70 °C
Merenje vrednosti protoka	At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Priključak na električnu mrežu	Connector Type B acc. to ISO 4400
min. radni pritisak	1,5 bar
Vrsta zaštite	IP 65
Telo ventila	Aluminium alloy



Napomena

Ostali podaci na upit.

Artikal

Naziv	Priključak	Priključak za odzračivanje	Protok (L/min)	Broj plana uključivanja	Napon	Upravljanje	Konstrukciona veličina
K- 07 15 02 47	M 5	M 5	300	35	24 V DC		100
K- 07 15 02 48	G 1/8	G 1/8	500	35	24 V DC		100
K- 07 15 02 49	G 1/8	G 1/8	750	35	24 V DC		200
K- 07 15 02 50	G 1/4	G 1/8	850	35	24 V DC		200
K- 07 15 02 51	G 1/4	G 1/4	1300	35	24 V DC		300
K- 07 15 02 52	G 3/8	G 1/4	1500	35	24 V DC		300
K- 07 15 02 53	G 1/2"	G 1/2"	2000	35	24 V DC		400
K- 07 15 02 54	M 5	M 5	300	35	230 V, 50 Hz		100
K- 07 15 02 55	G 1/8	G 1/8	500	35	230 V, 50 Hz		100
K- 07 15 02 56	G 1/8	G 1/8	750	35	230 V, 50 Hz		200
K- 07 15 02 57	G 1/4	G 1/8	850	35	230 V, 50 Hz		200
K- 07 15 02 58	G 1/4	G 1/4	1300	35	230 V, 50 Hz		300
K- 07 15 02 59	G 3/8	G 1/4	1500	35	230 V, 50 Hz		300
K- 07 15 02 60	G 1/2"	G 1/2"	2000	35	230 V, 50 Hz		400