


K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

HANSA FLEX

Osobine

| | |
|-----------------|--|
| Radni pritisak | Max. 6 bar (copper alloy), Max. 25 bar (stainless steel) |
| Ø zaptivača | 26 mm |
| Ø zaštitne cevi | 10 mm |
| Materijal | Copper alloy, CrNi-Steel 1.4571 |



Napomena

Ostali podaci na upit.

Opis

For bimetallic thermometers in the »High quality« series.

Artikal

| Naziv | Priključni navoj | Ugradna dužina | SW (mm) | Materijal |
|----------------|------------------|----------------|---------|-------------------|
| K- 07 20 11 35 | G 1/2 | L1 = 63 mm | 27 | Copper alloy |
| K- 07 20 11 36 | G 1/2 | L1 = 100 mm | 27 | Copper alloy |
| K- 07 20 11 37 | G 1/2 | L1 = 160 mm | 27 | Copper alloy |
| K- 07 20 11 38 | G 1/2 | L1 = 63 mm | 27 | CrNi steel 1.4571 |
| K- 07 20 11 39 | G 1/2 | L1 = 100 mm | 27 | CrNi steel 1.4571 |
| K- 07 20 11 40 | G 1/2 | L1 = 160 mm | 27 | CrNi steel 1.4571 |

Pribor

K-BIMETALLTHERMOMETER 52-2 Bimetallic thermometers