

Osobine

Radni pritisak	Max. 12 bar, maximum static working pressure (non-pulsating)
Radni pritisak utičnog naglavka i nastavka	0 to 35 bar
Protok vazduha	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +60 °C
Kućište, telo ventila	Nickel-plated brass
Ventil	Brass
Čaura za odbravljinjanje	Plastic
Opruga, sigurnosni prsten, čvijje, kugle	Stainless steel
Zaptivni materijal	NBR



Napomena

Ostali podaci na upit.

Opis

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Artikal

Naziv	Priklučak	Dužina (mm)	SW (mm)
K-07 35 02 98	G 1/4 male	55,4	22
K-07 35 02 99	G 3/8 male	55,4	22
K-07 35 03 00	G 1/2 male	58,3	24

Dodatni elementi

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,