

K-DMUF ALLGEMEIN

Pressure transmitters for universal industrial applications, nonlinearity 0.25%

HANSA FLEX

Osobine

Tip	S-20
Napon	DC 8 ... 36 V
Priključak na električnu mrežu	With right-angle connector acc. to DIN EN 175301-803 A
Vrsta zaštite	IP 65 acc. to EN 60529
Izlazni signal	4 to 20 mA, 2-wire
Nelinearnost	up to 0.25% of span
Temperatura medija	-30 °C to +100 °C
Temperatura okoline	-40 °C to +70 °C
Delovi koji dodiruju merni materijal	CrNi steel 1.4571
Kućičšte	CrNi steel 1.4571



Opis

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development. Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

Dodatne informacije

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Artikal

Naziv	Merni opseg	Navoj
K- 07 20 12 55	-1 / 0.0 bar	G 1/2
K- 07 20 12 56	0 - 0.4 bar	G 1/2
K- 07 20 12 57	0 - 1.0 bar	G 1/2
K- 07 20 12 64	0 - 4.0 bar	G 1/2
K- 07 20 12 67	0 - 6.0 bar	G 1/2
K- 07 20 12 58	0 - 10.0 bar	G 1/2
K- 07 20 12 60	0 - 16.0 bar	G 1/2
K- 07 20 12 62	0 - 25.0 bar	G 1/2
K- 07 20 12 65	0 - 40.0 bar	G 1/2
K- 07 20 12 68	0 - 60.0 bar	G 1/2
K- 07 20 12 59	0 - 100.0 bar	G 1/2
K- 07 20 12 61	0 - 160.0 bar	G 1/2
K- 07 20 12 63	0 - 250.0 bar	G 1/2
K- 07 20 12 66	0 - 400.0 bar	G 1/2
K- 07 20 12 69	0 - 600.0 bar	G 1/2