

### Osobine

Radni pritisak	Max. 10 bar (at +20 °C)
Tvrdća	52 Shore D±3
Kalibracija	External
Temperatura okoline	-35 °C to +80 °C
Materijal	poliuretan



### Napomena

Ostali podaci na upit.

### Opis

This externally calibrated plastic hose made of high-quality polyester PUR is extremely flexible with optimal mechanical characteristics and very high pressure resistance across a wide temperature range. It is permanently flexible, boasts very good resilience and can be laid with a narrow bending radius. Its other advantages include good abrasion resistance, very good low-temperature flexibility and very high elongation at break. The hose is also suitable for vacuum applications. It is resistant to many different oils and lubricants (a special resistance test is recommended in specific cases owing to the additives that are blended in by the manufacturers), aliphatic hydrocarbons and gases such as oxygen, ozone, helium, etc.

### Artikal

Naziv	Ø creva unutra (mm)	Ø creva spolja (mm)	Radius savijanja relevantno protokom (mm)	Boja	Dužina rolne (m)
K- 07 10 05 47	2,6	4,0	17	Natural	25
K- 07 10 05 49	3,1	5,0	15	Natural	100
K- 07 10 05 48	3,1	5,0	15	plava	100
K- 07 10 05 51	9,0	12,0	67	Natural	100
K- 07 10 05 52	9,0	12,0	67	crna	100
K- 07 10 05 54	9,8	14,0	72	Natural	50
K- 07 10 05 53	9,8	14,0	72	plava	50
K- 07 10 05 55	9,8	14,0	72	crna	50
K- 07 10 05 56	11,0	16,0	88	Natural	50
K- 07 10 05 57	11,0	16,0	88	crna	50