

# K-MV O (NO) V 24 V DC 1

Normally open, (NO), pilot-operated, 24 V DC

**HANSA FLEX**

## Osobine

Priključak na električnu mrežu	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Vrsta zaštite	IP 65
Temperatura medija	max. 80 °C when using water or oils; max. 90 °C when using with air
Opis navoja	G thread acc. DIN EN ISO 228-1
Kućište, sedište ventila	Brass
Unutrašnji delovi	Stainless steel
Zaptivka	FPM



## Napomena

Ostali podaci na upit.

## Opis

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Artikal

Naziv	Navoj	maks. radni pritisak (bar)	maks. radni pritisak (bar)	NW	A (mm)	B (mm)	C (mm)	Konstrukcija
K- 07 30 01 97	G 1/2	7	0,50	15,0	70,0	70,0	112,3	4
K- 07 30 01 98	G 3/4	7	0,50	20,0	70,0	82,0	120,8	4
K- 07 30 01 99	G 1	7	0,50	25,0	70,0	82,0	129,3	4