

K-VERL ROHR BASIS LP

Extension tube for basis blow guns

HANSA FLEX

Osobine

Radni pritisak	Max. 16 bar
Temperatura	-20 °C to +60 °C
Vazdušna cev	Nickel-plated brass



Napomena

Ostali podaci na upit.

Artikal

Naziv	Definicija	Navoj
K- 07 10 11 46	Blow pipe with standard nozzle, 90 mm, bent	G 1/4
K- 07 10 11 47	Extension tube with standard nozzle, 300 mm, straight	G 1/4
K- 07 10 11 48	Flexible extension tube with standard nozzle, 400 mm, bendable	G 1/4
K- 07 10 11 49	Extension tube with standard nozzle, 500 mm, straight	G 1/4
K- 07 10 11 50	Blow pipe with Star-Tip nozzle, 90 mm, bent	G 1/4
K- 07 10 11 53	Extension tube with Star-Tip nozzle, 300 mm, straight	G 1/4
K- 07 10 11 54	Extension tube with Star-Tip nozzle, 500 mm, straight	G 1/4

je oprema za sledeće proizvode

K-BASIS LP	Blow guns, stepless adjustment, for use with extension tubes
K-LP STUFENLOS REGULIERBAR	Blow guns, stepless adjustment, 90 mm tube
K-LP STUFENLOS REGULIERBAR GE	Blow guns, stepless adjustment, with noise-reducing Star-Tip nozzle, 90 mm tube