

# K-W90 AG-K ISO 7-1 VA

Male elbows, conical male thread acc. to ISO 7-1, stainless steel

**HANSA FLEX**

## Osobine

Područje pritiska	Max. 25 bar
preporučena creva	PTFE hose
Temperaturni opseg	-40 °C to +200 °C (depending on the hose quality and diameter)
Materijal	Plemeniti čelik 1.4404
Zaptivka	Pure metal



## Napomena

Ostali podaci na upit.

## Opis

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

## Artikal

Naziv	Navoj	za crevo	L1 (mm)	L2 (mm)	SW1 (mm)	SW2 (mm)
K- 07 40 30 32	R 1/8	6 mm / 4 mm	23,0	17,0	12	10
K- 07 40 30 33	R 1/8	8 mm / 6 mm	23,0	17,0	14	10
K- 07 40 30 30	R 1/4	6 mm / 4 mm	23,0	21,5	12	10
K- 07 40 30 31	R 1/4	8 mm / 6 mm	23,0	21,5	14	10
K- 07 40 30 29	R 1/4	10 mm / 8 mm	26,0	21,5	16	12