

# K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

**HANSA FLEX**

## Osobine

Mediji	Air, neutral gases, filtered
Radni pritisak	1.5 to 10 bar
Radna temperatura	-20 °C to +70 °C
Priključak na električnu mrežu	Plug connector PG 9
Sadržano u isporuci	Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws
Apsorbovanje snage	3 W=/5 VA~
Kućište	Aluminium, anodised
Zasun	Stainless steel
Zaptivni materijal	NBR



## Napomena

Ostali podaci na upit.

## Opis

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design. <br>Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.<br>

## Artikal

Naziv	Napon	Priključak	DN	Protok (L/min)
K- 07 15 00 05	230 V, 50 Hz	G 1/4	7	1250
K- 07 15 00 06	24 V DC	G 1/4	7	1250