



# K-BKR GELB STAHLHEBEL IG IG

Ball valves with yellow steel lever, lightweight type, female/female thread

**HANSA FLEX**

## Osobine

|                          |  |
|--------------------------|--|
| <b>Oblast primene</b>    | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture   |
| <b>Radni pritisak</b>    | Max. 40 bar  |
| <b>Radna temperatura</b> | -15 °C to +90 °C   |
| <b>Opis navoja</b>       | G thread acc. DIN EN ISO 228-1   |
| <b>Kućište</b>           | Nickel-plated brass  |
| <b>Poluga</b>            | Steel, with plastic coating  |
| <b>Kugla</b>             | Chrome-plated brass  |
| <b>Zaptivka kugle</b>    | PTFE   |
| <b>Zaptivka vretena</b>  | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM)<br>1 gasket (PTFE)<br>additional PTFE-gasket |



## Napomena

Ostali podaci na upit.

## Artikal

| Naziv          | DN | Navoj   | A<br>(mm) | B<br>(mm) | L<br>(mm) |
|----------------|----|---------|-----------|-----------|-----------|
| K- 07 30 00 81 | 8  | G 1/4   | 85,0      | 42,0      | 39,0      |
| K- 07 30 00 85 | 10 | G 3/8   | 85,0      | 42,0      | 43,0      |
| K- 07 30 00 89 | 15 | G 1/2   | 85,0      | 46,0      | 50,0      |
| K- 07 30 00 93 | 20 | G 3/4   | 105,0     | 53,0      | 58,0      |
| K- 07 30 00 97 | 25 | G 1     | 105,0     | 57,0      | 69,0      |
| K- 07 30 01 01 | 32 | G 1 1/4 | 130,0     | 70,0      | 81,0      |
| K- 07 30 01 05 | 40 | G 1 1/2 | 130,0     | 76,0      | 93,0      |
| K- 07 30 01 09 | 50 | G 2     | 165,0     | 92,0      | 110,0     |