
K-BKR LANG IG IG

Ball valves, long-threaded type, female/female thread



Osobine					
Oblast primene	Compressed air, water, non-toxic and non- corrosive gases, heating systems, agriculture				
Radni pritisak	Max. 40 bar				
Radna temperatura	-15 °C to +90 °C				
Opis navoja	Thread acc. to ISO 7-1				
Kućište	Nickel-plated brass				
Poluga	Aluminium, painted black				
Kugla	Chrome-plated brass				
Zaptivka kugle	PTFE				
Zaptivka vretena	NBR / EPDM				





Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211) Ostali podaci na upit.

Napomene u vezi porudžbine

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatne informacije

The pressure values refer to a maximum operating temperature of 40 °C. Lower maximum pressure apply at higher temperatures. See data sheet.

Artikal					
Naziv	DN	Navoj	A (mm)	B (mm)	L (mm)
K- 07 30 21 45	8	Rp/Rp 1/4	85,0	42,0	49,0
K- 07 30 21 46	10	Rp/Rp 3/8	85,0	42,0	50,0
K- 07 30 21 47	15	Rp/Rp 1/2	85,0	46,0	61,0
K- 07 30 21 48	20	Rp/Rp 3/4	105,0	53,0	70,0
K- 07 30 21 49	25	Rp/Rp 1	105,0	57,0	84,0
K- 07 30 21 50	32	Rp/Rp 1 1/4	130,0	70,0	97,0
K- 07 30 21 51	40	Rp/Rp 1 1/2	130,0	76,0	108,0
K- 07 30 21 52	50	Rp/Rp 2	165,0	92,0	130,0