

K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)

HANSA FLEX

Osobine

Tip	A-10
Napon	8 - 30 V
Priključak na električnu mrežu	With right-angle connector acc. to DIN EN 175301-803 A
Vrsta zaštite	IP 65 acc. to EN 60529
Izlazni signal	4 to 20 mA, 2-wire
Nelinearnost	0.5% of span
Temperatura medija	0 °C to +80 °C
Temperatura okoline	0 °C to +80 °C
Delovi koji dodiruju merni materijal	CrNi steel 1.4404
Kućiče	CrNi steel 1.4404



Napomena

Ostali podaci na upit.

Opis

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Dodatne informacije

Further measuring ranges on request

Pressure converter with output signal 0 - 10 V, 0 - 5 V and others on request.

Artikal

Naziv	Merni opseg	Navoj
K- 07 20 10 46	0 - 1.0 bar	G 1/4
K- 07 20 10 47	0 - 1.6 bar	G 1/4
K- 07 20 10 48	0 - 2.5 bar	G 1/4
K- 07 20 10 49	0 - 4.0 bar	G 1/4
K- 07 20 10 50	0 - 6.0 bar	G 1/4
K- 07 20 10 51	0 - 10.0 bar	G 1/4
K- 07 20 10 52	0 - 16.0 bar	G 1/4
K- 07 20 10 53	0 - 25.0 bar	G 1/4
K- 07 20 10 54	0 - 40.0 bar	G 1/4
K- 07 20 10 55	0 - 60.0 bar	G 1/4
K- 07 20 10 56	0 - 100.0 bar	G 1/4
K- 07 20 10 57	0 - 160.0 bar	G 1/4
K- 07 20 10 58	0 - 250.0 bar	G 1/4
K- 07 20 10 59	0 - 400.0 bar	G 1/4
K- 07 20 10 60	0 - 600.0 bar	G 1/4