

# K-TUE 7,2 7,8 MS NI

Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass

**HANSA FLEX**

## Osobine

|                    |   |
|--------------------|---|
| Radni pritisak     | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Temperatura medija | -20 °C to +100 °C   |
| Materijal          | Mesing, niklovan  |



## Napomena

Ostali podaci na upit.

## Artikal

| Naziv          | Definicija    |
|----------------|---------------|
| K- 07 35 01 76 | Stem, I.D. 6  |
| K- 07 35 01 88 | Stem, I.D. 8  |
| K- 07 35 01 77 | Stem, I.D. 9  |
| K- 07 35 01 89 | Stem, I.D. 10 |
| K- 07 35 01 84 | Stem, I.D. 13 |

## je dodatni element za sledeće proizvode

|                          |   |
|--------------------------|---|
| K-SVKM NW 7,8 AG H       | Quick disconnect couplings DN 7.8 - for extremely high flow rates, male           |
| K-SVKM NW 7,8 IG H       | Quick disconnect couplings DN 7.8 - for extremely high flow rates, female         |
| K-SVKM NW 7,8 SCHL TUE H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem |
| K-LKM S NW7,8 AG         | Safety couplings DN 7.8, male   |
| K-LKM S NW7,8 IG         | Safety couplings DN 7.8, female   |
| K-LKM S NW7,8 SCHL TUE   | Safety couplings DN 7.8, with hose stem   |