

K-SVKM NW 7,6 SCHL TUE ST VZ

Quick disconnect couplings DN 7.6, galvanised steel / brass, with hose connector

HANSA FLEX

Osobine

Radni pritisak	Max. 16 bar
Protok vazduha	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +100 °C
Kućište	Steel
Opruga	Stainless-steel
Klizna čaura	Hardened and nickel-plated steel
Zaptivni materijal	NBR



Napomena

Ostali podaci na upit.

Opis

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

Artikal

Naziv	Priključak	Dužina (mm)
K- 07 35 07 83	Stem, I.D. 6	67,0
K- 07 35 07 84	Stem, I.D. 8	70,0
K- 07 35 12 87	Stem, I.D. 9	70,0
K- 07 35 07 85	Stem, I.D. 10	70,0
K- 07 35 07 86	Stem, I.D. 13	68,0

Dodatni elementi

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel