

K-SVKM NW 5 IG MS NI

Quick disconnect couplings DN 5, nickel-plated brass, female

HANSA FLEX

Osobine

| | |
|----------------------------------|---|
| Radni pritisak | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Protok vazduha | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura medija | -20 °C to +100 °C |
| Kučište, čaura, telo ventila | Nickel-plated brass |
| Opruga, sigurnosni prsten, kugle | Stainless steel |
| Zaptivni materijal | NBR |



Napomena

Ostali podaci na upit.

Opis

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Artikal

| Naziv | Priključak | Dužina (mm) | SW (mm) |
|----------------|--------------|-------------|---------|
| K- 07 35 06 59 | G 1/8 female | 38,0 | 14 |
| K- 07 35 06 61 | G 1/4 female | 38,0 | 17 |
| K- 07 35 06 60 | G 3/8 female | 40,0 | 19 |