

K-SVKM NW 7,2 SCHL-TUE VA

Quick disconnect couplings DN 7.2, stainless steel, with hose stem

HANSA FLEX

Osobine

Radni pritisak	1 - 35 bar and rough vacuum
Protok vazduha	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-25 °C to +200 °C
Kućište, čaura, telo ventila	Stainless steel 1.4305
Opruga, sigurnosni prsten	Stainless steel 1.4310
Zaporne čivije	Stainless steel 1.4401
Zaptivni materijal	FKM



Napomena

Ostali podaci na upit.

Opis

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

Artikal

Naziv	Priključak	Dužina (mm)	SW (mm)
K- 07 35 07 65	Stem, I.D. 6	59,0	22
K- 07 35 12 65	Stem, I.D. 8	59,0	22
K- 07 35 07 66	Stem, I.D. 9	59,0	22
K- 07 35 12 66	Stem, I.D. 10	59,0	22
K- 07 35 07 67	Stem, I.D. 13	59,0	22

Dodatni elementi

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305