

# K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

**HANSA FLEX**

## Osobine

Radni pritisak	0 - 35 bar
Protok vazduha	2.100 l/min (at $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +40 °C
Navojni deo	Nickel-plated brass
Telo ventila	Steel, QPQ treated
Čaura za odbravljivanje	Extremely robust, ergonomic plastic
Ventil, sedište	Brass
Mediji	Only for clean compressed air
Zaptivke	NBR
Opruga, sigurnosni prsten, kugle	stain less steel



## Napomena

Ostali podaci na upit.

## Opis

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

## Artikal

Naziv	Priključak	Dužina (mm)	SW (mm)
K- 07 35 08 47	G 1/4 male	65,0	19
K- 07 35 08 48	G 3/8 male	65,0	19
K- 07 35 08 49	G 1/2 male	59,0	22

## Dodatni elementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass