

# K-SVKM NW 7,8 AG VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, male

**HANSA FLEX**

## Osobine

Radni pritisak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok vazduha	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-15 °C to +200 °C
Kućište, čaura, telo ventila	Stainless steel 1.4305
Opruga, sigurnosni prsten, kugle	Stainless steel
Zaptivni materijal	FKM



## Napomena

Ostali podaci na upit.

## Opis

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

## Artikal

Naziv	Priključak	Dužina (mm)	SW (mm)
K- 07 35 07 90	G 1/4 male	59,5	19
K- 07 35 07 91	G 3/8 male	57,5	19
K- 07 35 07 92	G 1/2 male	60,5	24

## Dodatni elementi

K-NIPPEL KUPPL NW7 AG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 1	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305