


# K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

**HANSA FLEX**

## Osobine

|                                  |   |
|----------------------------------|---|
| Radni pritisak                   | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Protok vazduha                   | 700 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Temperatura medija               | -20 °C to +100 °C   |
| Kućište, čaura, telo ventila     | Brass   |
| Opruga, sigurnosni prsten, kugle | Stainless steel   |
| Zaptivni materijal               | NBR   |



## Napomena

Ostali podaci na upit.

## Opis

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

## Artikal

| Naziv          | Priključak    | Dužina (mm) | SW (mm) |
|----------------|---------------|-------------|---------|
| K- 07 35 07 56 | Stem, I.D. 6  | 58,0        | 21      |
| K- 07 35 12 72 | Stem, I.D. 8  | 58,0        | 21      |
| K- 07 35 07 57 | Stem, I.D. 9  | 58,0        | 21      |
| K- 07 35 12 74 | Stem, I.D. 10 | 58,0        | 21      |
| K- 07 35 07 58 | Stem, I.D. 13 | 58,0        | 21      |