

# K-LKM S NW7,8 SCHL TUE

Safety couplings DN 7.8, with hose stem

**HANSA FLEX**

## Osobine

Radni pritisak	maks. 20 bara
Protok vazduha	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +100 °C
Priključak tela ventila	Nickel-plated brass
Opruga, kugle	Stainless-steel
Klizna čaura	Anodised aluminium
Čaura za odbravljivanje	Hardened and nickel-plated steel
Zaptivni materijal	NBR



## Napomena

Ostali podaci na upit.

## Opis

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

## Artikal

Naziv	Priključak	Dužina (mm)
K- 07 35 08 88	Stem, I.D. 6	86,0
K- 07 35 12 96	Stem, I.D. 8	86,0
K- 07 35 08 89	Stem, I.D. 9	86,0
K- 07 35 12 97	Stem, I.D. 10	86,0
K- 07 35 08 90	Stem, I.D. 13	86,0

## Dodatni elementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass